15

## WHAT IS CLAIMED IS:

A composite structure, comprising:

- a foam sheet comprising polyolefin; and
- Sub AI a coating disposed on at least one surface of said polyolefin b. foam sheet, said coating comprising at least one member selected from the group consisting of ethylene/propylene rubber, homogeneous ethylene/alpha-olefin copolymer, and ethylene/acrylic acid copolymer,

whereby, said coating is capable of bonding said polyolefin foam sheet to a second foam sheet having a different chemical composition than said polyolefin foam sheet at a bond strength of at least about 4 lb<sub>f</sub>/inch.

- 2. The composite structure of claim 1, wherein said bond strength is at least about 4.5 lb<sub>f</sub>/inch.
- 3. The composite structure of claim 1, wherein said polyolefin foam sheet comprises polyethylene homopolymer or copolymer and said second foam sheet comprises polypropylene homopolymer or copolymer.
- 20 The composite structure of claim 1, wherein said polyolefin foam 4. sheet comprises polypropylene homopolymer or copolymer and said second foam sheet comprises polyethylene homopolymer or copolymer.
- 5. The composite structure of claim 1, wherein said coating comprises 25 ethylene/propylene rubber.
  - 6. The composite structure of claim 1, wherein said coating is substantially solventless.

20

25

- 7. The composite structure of claim 1, wherein said polyolefin foam sheet comprises polyethylene homopolymer or copolymer having a density ranging from about 0.4 to about 15 pounds/ft<sup>3</sup>.
- 5 8. The composite structure of claim 1, wherein said polyolefin foam sheet comprises polypropylene homopolymer or copolymer having a density ranging from about 0.5 to about 10 pounds/ft<sup>3</sup>.
- 9. The composite structure of claim 1, further including a second foam sheet comprising a material of a different chemical composition than said polyolefin foam sheet and bonded by said coating to said polyolefin foam sheet at a bond strength of at least about 4 lb<sub>f</sub>/inch.
  - 10. The composite structure of claim 9, wherein said polyolefin foam sheet comprises polyethylene homopolymer or copolymer and said second foam sheet comprises polypropylene homopolymer or copolymer.
  - 11. The composite structure of claim 9, wherein said polyolefin foam sheet comprises polypropylene homopolymer or copolymer and said second foam sheet comprises polyethylene homopolymer or copolymer.
  - 12. A multilayer composite structure, comprising:
  - a. a first foam layer comprising polyethylene homopolymer or copolymer;
  - b. a second foam layer comprising polypropylene homopolymer or copolymer; and
  - c. a coating disposed between and bonding said first and second foam layers together at a bond strength of at least about 4  $lb_f$ /inch, said coating comprising at least one member selected from the group consisting

30

of ethylene/propylene rubber, homogeneous ethylene/alpha-olefin copolymer, and ethylene/acrylic acid copolymer.

- 13. The composite structure of claim 12, wherein said coating comprises5 ethylene/propylene rubber.
  - 14. The composite structure of claim 12, wherein said coating is substantially solventless.
- 10 15. The composite structure of claim 12, wherein said first foam layer comprises low density polyethylene.
  - 16. The composite structure of claim 12, wherein said first foam layer has a density ranging from about 0.4 to about 15 pounds/ft<sup>3</sup>.
  - 17. The composite structure of claim 12, wherein said second foam layer comprises polypropylene homopolymer.
- 18. The composite structure of claim 12, wherein said second foam layer 20 has a density ranging from about 0.5 to about 10 pounds/ft<sup>3</sup>.
  - 19. The composite structure of claim 12, wherein the bond strength between said first and second foam layers is at least about  $4.5 \, \mathrm{lb_f/inch.}$
- 25 20. The composite structure of claim 12, wherein said structure is in the form of a bodyboard flotation article.
  - 21. The composite structure of claim 20, wherein said polyethylene foam layer has a thickness ranging from about 1/16 to about 1 inch and said polypropylene foam has a thickness ranging from about 1 to about 4 inches.

25

10

- 22. A method for making a composite structure, comprising:/
  - a. providing a foam sheet comprising polyolefin; and
- b. coating at least one surface of said polyolefin foam sheet, said coating comprising at least one member selected from the group consisting of ethylene/propylene rubber, homogeneous ethylene/alpha-olefin copolymer, and ethylene/acrylic acid copolymer.

whereby, said coating is capable of bonding said polyolefin foam sheet to a second foam sheet having a different chemical composition than said polyolefin foam sheet at a bond strength of at least about  $4 \, \mathrm{lb_f/inch.}$ 

- 23. The method of claim 22, wherein said bond strength is at least about 4.5 lb<sub>f</sub>/inch.
- 15 24. The method of claim 22, wherein said polyolefin foam sheet comprises polyethylene homopolymer or copolymer and said second foam sheet comprises polypropylene homopolymer or copolymer.
  - 25. The method of claim 22, wherein said polyolefin foam sheet comprises polypropylene homopolymer or copolymer and said second foam sheet comprises polyethylene homopolymer or copolymer.
  - 26. The method of claim 22, wherein said coating comprises ethylene/propylene rubber.
  - 27. The method of claim 22, wherein said polyolefin foam sheet comprises polyethylene homopolymer or copolymer having a density ranging from about 0.4 to about 15 pounds/ft<sup>3</sup>.

15

- The method of claim 22, wherein said polyolefin foam sheet comprises 28. polypropylene homopolymer or copolymer having a density ranging from about 0.5 to about 10 pounds/ft3.
- 5 The method of claim 22, wherein said coating is substantially 29. solventless.
  - The method of claim 22, further including the step of bonding a 30. second foam sheet to said polyolefin foam sheet via said coating, said second foam sheet comprising a material of a different chemical composition than said polyolefin foam sheet.
  - The method of claim 30, wherein said polyolefin foam sheet comprises 31. polyethylene homopolymer or copolymer and said second foam sheet comprises polypropylene homopolymer or copolymer.
  - The method of claim 30, wherein said polyolefin foam sheet comprises 32. polypropylene homopolymer or copolymer and said second foam sheet comprises polyethylene homopolymer or copolymer.

25